

PA: PADS™ In-Wall Amplifiers and Receivers



PA-15R

PA-15RI

Power: 15, 30, or 48 Watts
Dimensions: 1.75" W x 4" H x 3" D
Dials: rotary or slider volume control
Options: IR detector, local source input, and doorbell/paging unit

The Pragmatic PA series of in-wall amplifiers and receivers with volume control receives line level stereo audio signals and amplifiers to drive speakers. It can fit in a single gang and comes with a variety of options including a built-in infra-red detector, rotary or slider volume controls, local source input and doorbell/ paging input. It is also available in 15 Watts, 30 Watts, and 48 Watts total continuous output power.

The PA 15R / PA 30R / PA 48R units receive line level stereo audio signals and amplifiers to drive speakers and use a rotary dial for volume. The PA 15RI / PA 30RI / PA 48RI units are similar to PA XXR but add IR detector, local source input and doorbell / paging input. The PA 15S / PA 30S / PA 48S units receive line level stereo audio signals and amplifiers to drive speakers and use a slider volume control. The PA 15SI / PA 30SI / PA 48SI units are similar to PA XXS, but add IR detector, local source input and door-bell / paging input.

Applications:

Audio transmission in schools, universities, businesses, department stores, etc.
 Residential applications for intercom, music distribution, etc.

Ideal for new construction or retrofit applications on existing structured wires
 Receives line level stereo audio signals and amplifiers to drive speakers

Features and Benefits:

Comes with a variety of options including:
 15, 30 or 48 Watts
 IR detector
 Doorbell/paging unit
 Rotary or slider volume controls

Architect Specifications:

The unit shall consist of an in-wall unit that receives line level stereo audio signals and amplifiers to drive speakers. It shall have the options of 15, 30 or 48 Watts, an IR detector, a doorbell / paging unit, and a rotary or slider volume control. It shall measure 1.75" W x 4" H x 3" D and fit in a single gang.

The unit shall be a Pragmatic PADS™ PA In-wall amplifier and receiver.

Copyright © 1994- 2007. All rights reserved.

Pragmatic Communications Systems, Inc.

2934 Corvin Drive, Santa Clara, CA 95051, USA

Tel. (408) 735 0300

Fax. (408) 735 0800

www.pragmatic1.com