

Pragmatic Communications Systems, Inc.

WVT-1 Wireless Video Transmitter

System Components :

- WVT-1 Transmitter with internal PC board antenna
- AC-DC wall plug power adapter

Features :

- Transmission range : 300-600 ft. w/ 50,000 μ V/m @ 3 meters
- DC supply for transmitter : 7.2 - 15 VDC @ 15 mA
- Compact in size : 1.0" H X 2.4" W X 2.2" L
- Works with color or B&W camera signals
- Input Video level : 1.0 V @ 75 Ω (NTSC, PAL, SECAM)
- Transmitter frequency range : 902 - 928 MHz.
- Video Bandwidth > 5 MHz.
- FCC Part 15 certified

Applications :

- Remote surveillance
- Video conferencing
- Mobile video coverage
- Remote video recording
- Video broadcast on campus
- Covert video transmission
- High performance wireless video network
- Law enforcement - ATF / CIA / DEA / FBI / INS
- Aerial photography from RC helicopters / airplanes



Accessories / Options :

- CLA-12 Cigarette Lighter Adapter for Auto
- BATT-1 Rechargeable Battery Pack - 7.2 VDC
- CLCD 4" Color LCD Video Monitor
- WATX Wireless Audio Transmitter (Factory Installed option)

For price and availability, please call Pragmatic Communications Systems, Inc.
Quantity discount available

2934 Corvin Drive, Santa Clara, CA 95051 Phone (408) 735-0300 FAX (408) 735-0800