

» PLP-63UH4K

Pragmatic Native 4K Laser 3-LCD Projector

Simple, Powerful, Affordable Laser Projector

- ✓ Energy efficient high-performance design
- ✓ 6300 ANSI lumens brightness
- ✓ 3840 x 2160 @ 60Hz Native resolution
- ✓ High-reliability, high-efficiency laser light source
- ✓ Designed for 24 hours x 7 days continuous usage
- ✓ Interchangeable lens for widest throw ratio
- ✓ 3-LCD TFT Active Matrix MLA display engine
- ✓ 20,000/30000 hours of trouble-free operation
- ✓ Multiple video input formats and connectors
- ✓ Optional device control via RS-232, IR or network
- ✓ High brightness and wider color gamut
- ✓ Horizontal and vertical keystone correction
- ✓ Optical zoom, vertical lens shift
- ✓ Lower total cost of ownership (TCO)



TO PLACE an ORDER or for QUESTIONS,
Email Us: sales@pragmatic1.com or Call Us: (408) 748-1100

Digital Signage In: Hospitals, Pharmacies, Medical clinic, Shopping Malls, Hotel Lobbies, Restaurants, Boutique shops, College campus, Sports Bar, Health & Fitness Clubs, Retail stores, Casinos, etc.

Cost Effective / Energy Efficient Design

The PLD-63UH4K laser projector is a very cost-effective, energy-efficient unit for deployment in cost sensitive digital signage applications.

- Professional laser light source for 20000 hours / 30000 hours ECO
- High brightness and color stability system

RELATED PRODUCTS

- PDP-1 Pragmatic Digital Signage player
- PLP-83HD laser projector
- PVP-72A laser projector
- PLP-63HD laser projector
- PHA (compact directional line-array speakers)
- SAA (compact Stereo Audio Amplifier)
- MBA (compact mono-block Audio Amplifier)
- PTS-4077F Directional drop-tile, ceiling speaker

Specifications

DISPLAY TECHNOLOGY	3-LCD TFT Active Matrix 3 x 0.64" with MLA (Micro Lens Array)
NATIVE RESOLUTION	3840x2160 @60Hz
LIGHT SOURCE	Laser light source
BRIGHTNESS	6300 ANSI lumens
CONTRAST RATIO	5,000,000:1
KEystone CORRECTION	Four Corner correction, Horizontal +/- 25° & Vertical +/- 30°
VIDEO RESOLUTIONS	640x480i/p, 800x600i/p, 1024x768i/p, 1280x1024i/p, 1280x768i/p, 1366x768i/p, 1920x1080i/p, 1920x1200@60Hz, 3840x2160@60p
THROW RATIO	1.08-1.76:1, optional lenses:1.2 - 2.01:1, 1.35-1.63:1
SCREEN ROTATION	Landscape, portrait (+90°, -90°)
VIDEO INPUT CONNECTIONS	HDMI 2X, HDBaseT (optional), USB 2X,
AUDIO OUTPUT CONNECTION	3.5mm Stereo jack, SPDIF Audio OPTICAL out
CONTROL INTERFACE PORTS	RS-232 input/output, 100Base-T/10Base-T RJ-45, IR control
POWER	100V-240V AC, 360W active, less than 0.5W standby mode
OPERATING CONDITIONS	Temperature 41°-104°F (5°- 40°C), Humidity 20-80% (non-condensing)
DIMENSIONS (HxWxD)	15.35" x 11.57" x 5.04" (390mm x 294mm x 128mm)
WEIGHT	11.46 lbs (5.2 kg)
REGULATIONS	CE, RoHS
PACKAGE CONTENTS	Projector unit, IR remote control, AC power cord
WARRANTY	One year limited warranty on parts and labor



TO PLACE an ORDER or for QUESTIONS,
Email Us: sales@pragmatic1.com or Call Us: (408) 748-1100